



Advantages:

- Space saving for low cabinets!
Connected by straight PFA-Tube (eliminates curves), if tubing connects through the side or the back of the cabinet.

Elements:

material	• PE natural • CDP electrical conductive • PVDF
O-ring	• Perfluorelastomer (Kalrez®)
Dimension	• Total height: 180mm
Connection sizes	• Connection for chemical Flare 1/2", 3/4", NPT (Special connection variations and sizes on request) • Connection gas Flare 1/4", 3/8", 1/2"
Article number	• DH-DK-PE-XXX-HFX/X"-FX/X"

Additional Quick Connect Accessories:

Description	Part Number
Universal wrench	RDH-89740
particle filter	RDH-89905
dust protection cap	RDH-69913
seal cap	RDH-89740
originality safety system	RDH-69320
stopper with degassing	
valve	RDH-69314
docking station	RDC-89740
coding-checker	RDH-89701-02
flaring tools for	
Flaretek® connection	13004
Flaretek® elbow fitting 90°	E8-4FN-1



QC-System – a product from AS Strömungstechnik GmbH | www.asstroemungstechnik.de

Dr. Claus Dusemund | Dusemund Pte Ltd. | 25 international business park | #04-62 german centre
singapore 609916 | tel (+65) 6562 7871 | fax (+65) 6562 7872 | mobile: (+65) 96782568
e-mail claus@dusemund.com | <http://www.dusemund.com>

